



MATERIALS TO BE USED:

- HOT MIX ASPHALT SURFACE COURSE, MIX, "C", N50
- BITUMINOUS MATERIAL (PRIME COAT), 0.5 GAL/SY
- HOT MIX ASPHALT BINDER COURSE, IL-19, N50
- BITUMINOUS MATERIAL (PRIME COAT), 0.5 GAL/SY
- AGGREGATE BASE COURSE, CA-6 CRUSHED LIMESTONE
- 6 TO 6.5 OZ/SY WOVEN STABILIZER FABRIC AT DIRECTION OF VILLAGE ENGINEER

NOTES:

1. MAY BE SUBJECT TO STATE OR COUNTY PERMIT.
2. ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH MOST RECENT I.D.O.T. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
3. PROOF ROLL REQUIRED UPON COMPLETION OF SUB GRADE AND BASE MATERIAL. ANY SOFT AREAS FOUND SHALL BE UNDERCUT TO A MINIMUM 1-FOOT AND BACKFILLED WITH CA-1, 3" LIMESTONE.
4. PAVEMENT SHOULD BE DESIGNED IN ACCORDANCE WITH THE EXPECTED VEHICULAR LOADS. ABOVE REFERENCED DESIGN IS A MINIMUM STANDARD.
5. REFER TO 10-11-8-2 OF VILLAGE CODE FOR OTHER SPECIFIC PARKING LOT CONSTRUCTION REQUIREMENTS.



VILLAGE OF BENSENVILLE
 12 S. CENTER STREET
 BENSENVILLE, IL 60106
 WWW.BENSENVILLE.IL.US

**PARKING LOT PAVEMENT
 STANDARD**

VILLAGE OF BENSENVILLE SPECIFICATIONS AND DETAILS		REVISIONS	
FILE LOCATION			
G:\ENGINEERING\ STANDARDS\ NEW STANDARDS\ROADWAY			